



**GLOBAL
INDUCTION
LIGHTING US**



Global Induction Lighting US

917 SE 14th St, Fort Lauderdale, FL 33316

info@gilus.us • 954-467-8478 • www.gilus.us

VEL per watt based on mean lumens

	mean lumens per watt	VEL at 5000K with S/P ratio 1.96	VEL at 6500K with S/P ratio 2.25
Global GLTL 100W Tunnel Light, 120-277v	78.0	152.88	175.5
Global GLTL 150W Tunnel Light, 120-277v	78.0	152.88	175.5
Global GLTL 200W Tunnel Light, 120-277v	80.0	156.8	180
Global GLTL 250W Tunnel Light, 120-277v	82.0	160.72	184.5
Global GLTL 400W Tunnel Light, 120-277v	82.0	160.72	184.5
Global GLIN 400W Indoor Light, Poly Lens, 120-277v, Square	82.0	160.72	184.5
Global GLIN 100W Indoor Light, Poly Lens, 120-277v, Square	78.0	152.88	175.5
Global GLIN 150W Indoor Light, Poly Lens, 120-277v, Square	78.0	152.88	175.5
Global GLWP 85W Wall Pack, 5000K, 120-277v	76.0	148.96	171
Global GLWP 100W Wall Pack, 5000K, 120-277v	78.0	152.88	175.5
Global GLWP Wallpack-Small 40 Watt	76.0	148.96	171
Global GLWP Wallpack-Large 80 Watt	76.0	148.96	171
Global GLWP Wallpack-Large 120 Watt	78.0	152.88	175.5

	mean lumens	mean lumens per watt	S/P	VEL per watt
Metal Halide Clear 400W	25,600	64.00	1.49	95.4
High Pressure Sodium Clear 400W	45,000	112.50	0.62	69.8
T12 Instant Start F96T12/LW 60W	5,430	90.50	1	90.5
T8 Rapid Start F032/730 32W	3,420	106.88	1.62	173.1
T5 HO 54W	4,370	80.93	1.62	131.1