



**GLOBAL
INDUCTION
LIGHTING US**



Global Induction Lighting US

917 SE 14th St, Fort Lauderdale, FL 33316

info@gilus.us • 954-467-8478 • www.gilus.us

INTERIOR LIGHTING

Highbay Prismatic

IP RATING
43



GLDL-200/250

Features

- ◆ High temperature-resistant polycarbonate reflector.
- ◆ UV stabilized polycarbonate lens fastened with clamp band.
- ◆ Die cast aluminum ballast casing with white powder coated finish for corrosion-resistance.
- ◆ Highbays are equipped with an inner reflector for maximum light.
- ◆ Includes 5 feet of cabtyre (cord) with strain relief clamp.

Lamp and Ballast

- ◆ Globals 200W or 250W round tubular induction lamp features high lighting efficiency.
- ◆ Note: Total energy consumption=fixture wattage+5% for ballast overhead.
- ◆ Estimated lifespan 100,000 hours.
- ◆ Electronic ballast features high power factor (>0.95), flicker free, instant on/instant re-strike.
- ◆ Ambient temperature for lighting fixture:-40C~+40C.

Applications

- ◆ Workshops, warehouses, airports, stations, retail showrooms, exhibition halls, arenas and factories.


HIGHBAY PRISMATIC

DIMENSIONS



PHOTOMETRICS

Dimensions:

Unit: in. (mm)



Model No.	D	D1	H
GLDL 200	Ø23.82(605)	Ø9.61(244)	~28.23(717)
GLDL 250	Ø23.82(605)	Ø11.02(280)	~28.74(730)



GLDL - 200 / 250

FIXTURE SPECIFICATIONS

Global Code	Type	Lamp	Voltage	Colour Temp.#	Notes:
GLDL-200	Prismatic Highbay	200W - Round	120~277	6500K	#Colour temperatures of 4100K or 5000K available by special order
GLDL-250		250W - Round	208~347		